



TOOLING LIQUID

Technical Datasheet

Date:23/08/2023

Description

A specifically formulated, ready to use solution for wet tooling of all types of sealants, to produce a smooth, professional finish.

Directions for use

Lightly spray the joint needing to be tooled with SILTECH Tooling Liquid and smooth out with an appropriate tool, or finger sprayed/dipped with SILTECH Tooling Liquid.

Storage

Keep in a cool, dry and well ventilated area at ambient temperatures.

Caution

Keep out of reach of children. Avoid contact with eyes.

First aid measures

Eye Contact:

Causes mild irritation. Flush with plenty of water and seek medical attention if irritation occurs.

Skin Contact:

May cause mild irritation with prolonged contact. Wear protective gloves if required. Wash away with water.

Ingestion:

May cause nausea and vomiting. Drink water and do not induce vomiting. Seek medical attention if required.

Note

Avoid excessive application to the sealant surface, as this may result in a residue that could effect paintability of the sealant. Surface may be wiped with a damp cloth once skin has sufficiently cured. Do not allow the Tooling Liquid to enter between the sealant and surface, as this may result in a lack of adhesion.

Disclaimer:

The information provided in this Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.